

Model Porto	60	80	100	120	160
(mm)					
min-max (W)	50 - 600	50 - 800	50 - 1000	50 - 1200	50 - 1600
min-max (l - feeder manual)	40 - no limit	40 - no limit	40 - no limit	40 - no limit	40 - no limit
min-max (l - feeder auto)	50 - 700	50 - 700	50 - 700	50 - 700	50 - 700
min-max (a - feeder manual)	30 - no limit	30 - no limit	30 - no limit	30 - no limit	30 - no limit
min-max (a - feeder auto)	30 - 700	30 - 700	30 - 700	30 - 700	30 - 700
min (b)	50	50	50	50	50
min for Porto S x/x1	35/35	35/35	35/35	35/35	35/35
min for Porto M x/x1	0/35	0/35	0/35	0/35	0/35
min for Porto L x/x1	0/0	0/0	0/0	0/0	0/0

Dimensions depend on the equipment and the appropriate configuration of the machine

Model Porto	60	80	100	120	160
(in)					
min-max (W)	1.97 - 23.62	1.97 - 31.50	1.97 - 39.37	1.97 - 47.24	1.97 - 62.99
min-max (l - feeder manual)	1.57 - no limit	1.57 - no limit	1.57 - no limit	1.57 - no limit	1.57 - no limit
min-max (l - feeder auto)	1.97 - 27.56	1.97 - 27.56	1.97 - 27.56	1.97 - 27.56	1.97 - 27.56
min-max (a - feeder manual)	1.18 - no limit	1.18 - no limit	1.18 - no limit	1.18 - no limit	1.18 - no limit
min-max (a - feeder auto)	1.18 - 27.56	1.18 - 27.56	1.18 - 27.56	1.18 - 27.56	1.18 - 27.56
min (b)	1.97	1.97	1.97	1.97	1.97
min for Porto S x/x1	1.38/1.38	1.38/1.38	1.38/1.38	1.38/1.38	1.38/1.38
min for Porto M x/x1	0/1.38	0/1.38	0/1.38	0/1.38	0/1.38
min for Porto L x/x1	0/0	0/0	0/0	0/0	0/0

Dimensions depend on the equipment and the appropriate configuration of the machine

Model Porto	60	80	100	120	160
Processed materials					
Carton board max*	120 g/m ³	120 g/m ³	120 g/m ³	120 g/m ³	120 g/m ³
Corrugated flute type*	B-C-BC-BE-E	B-C-BC-BE-E	B-C-BC-BE-E	B-C-BC-BE-E	B-C-BC-BE-E
Max product height	to 35 mm	to 35 mm	to 35 mm	to 35 mm	to 35 mm
Technical Data					
Voltage	230 / 400	230/400	230/400	400	400
Motor Power kW *	0,75 - 5	0,75 - 5	0,75 - 5	0,75 - 5	0,75 - 5
Speed feeder manual	40 m/min	40 m/min	40 m/min	40 m/min	40 m/min
Inching speed **	do 120 m/min	do 120 m/min	do 120 m/min	do 120 m/min	do 120 m/min
Length * (m)	od 2 do 7	od 2 do 7	od 2 do 7	od 2 do 7	od 2 do 7
Net weight t *	od 0,35 do 1,5	od 0,35 do 1,5	od 0,35 do 1,5	od 0,35 do 1,5	od 0,35 do 1,5

* Version with an automatic feeder

** Parameters depend on the machine configuration

Model Porto	60	80	100	120	160
Processed materials					
Carton board max*	120 g/m ³	120 g/m ³	120 g/m ³	120 g/m ³	120 g/m ³
Corrugated flute type*	B-C-BC-BE-E	B-C-BC-BE-E	B-C-BC-BE-E	B-C-BC-BE-E	B-C-BC-BE-E
Max product height	do 35 mm	do 35 mm	do 35 mm	do 35 mm	do 35 mm
Technical Data					
Voltage	230 / 400	230/400	230/400	400	400
Motor Power kW *	0,75 - 5	0,75 - 5	0,75 - 5	0,75 - 5	0,75 - 5
Speed feeder manual	131.23 ft/min	131.23 ft/min	131.23 ft/min	131.23 ft/min	131.23 ft/min
Inching speed **	to 393.70 ft/min	to 393.70 ft/min	to 393.70 ft/min	to 393.70 ft/min	to 393.70 ft/min
Length * (ft)	from 6.56 to 22.97	from 6.56 to 22.97	from 6.56 to 22.97	from 6.56 to 22.97	from 6.56 to 22.97
Net weight t *	from 0,35 to 1,5	from 0,35 to 1,5	from 0,35 to 1,5	from 0,35 to 1,5	od 0,35 do 1,5

* Version with an automatic feeder

** Parameters depend on the machine configuration