

| | | Flat packaging | | | | | |
|-------------|--------------|-----------------|--------------|--------------|--------------|--------------|--------------|
| | | Model Vario ECO | 60 | 80 | 100 | 115 | 120 |
| | | (mm) | | | | | |
| | | min-max (W) | 50 - 600 | 50 - 800 | 50 - 1000 | 50 - 1150 | 50 - 1200 |
| | | min-max (L) | 75 - 800 | 75 - 900 | 75-900 | 75 - 900 | 75 - 900 |
| | | min-max (a) | 30 - 800 | 30 - 900 | 30 - 900 | 30 - 900 | 30 - 900 |
| | | min (b) | 50 | 50 | 50 | 50 | 50 |
| | | min x / x1 | 0/35 | 0/35 | 0/35 | 0/35 | 0/35 |
| | | min x / x1* | 0/0 | 0/0 | 0/0 | 0/0 | 0/0 |
| | | (in) | | | | | |
| | | min-max (W) | 1.97 - 23.62 | 1.97 - 31.50 | 1.97 - 39.37 | 1.97 - 45.28 | 1.97 - 47.24 |
| | | min-max (L) | 2.95 - 31.50 | 2.95 - 35.43 | 2.95-35.43 | 2.95 - 35.43 | 2.95 - 35.43 |
| min-max (a) | 1.18 - 31.50 | 1.18 - 35.43 | 1.18 - 35.43 | 1.18 - 35.43 | 1.18 - 35.43 | | |
| min (b) | 1.97 | 1.97 | 1.97 | 1.97 | 1.97 | | |
| min x / x1 | 0/1.38 | 0/1.38 | 0/1.38 | 0/1.38 | 0/1.38 | | |
| min x / x1* | 0/0 | 0/0 | 0/0 | 0/0 | 0/0 | | |

The formats depend on the configuration and equipment of the machine
*Option

| Model Vario ECO | 60 | 80 | 100 | 115 | 120 |
|-----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|
| Processed materials | | | | | |
| Carton board max | 120 g/m ³ | 120 g/m ³ | 120 g/m ³ | 120 g/m ³ | 120 g/m ³ |
| Corrugated flute type | B-C-BC-BE-E | B-C-BC-BE-E | B-C-BC-BE-E | B-C-BC-BE-E | B-C-BC-BE-E |
| Technical Data | | | | | |
| Voltage | 400 | 400 | 400 | 400 | 400 |
| Motor Power kW * | 0,75 - 5 | 0,75 - 5 | 0,75 - 5 | 0,75 - 5 | 0,75 - 5 |
| Speed | 20 - 100 m/min | 20 - 100 m/min | 20 - 100 m/min | 20 - 100 m/min | 20 - 100 m/min |
| Length * (m) | 5-10 | 5-10 | 5-10 | 5-10 | 5-10 |
| Net weight* (t) | 3-6 | 3-6,5 | 3,5-7 | 3,5-7,5 | 3,5-7,5 |

* p-arametry zależne od konfiguracji maszyny

| Model Vario ECO | 60 | 80 | 100 | 115 | 120 |
|-----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|
| Processed materials | | | | | |
| Carton board max | 120 g/m ³ | 120 g/m ³ | 120 g/m ³ | 120 g/m ³ | 120 g/m ³ |
| Corrugated flute type | B-C-BC-BE-E | B-C-BC-BE-E | B-C-BC-BE-E | B-C-BC-BE-E | B-C-BC-BE-E |
| Technical Data | | | | | |
| Voltage | 400 | 400 | 400 | 400 | 400 |
| Motor Power kW * | 0,75 - 5 | 0,75 - 5 | 0,75 - 5 | 0,75 - 5 | 0,75 - 5 |
| Speed | 65.62-328.08 ft/min | 65.62-328.08 ft/min | 65.62-328.08 ft/min | 65.62-328.08 ft/min | 65.62-328.08 ft/min |
| Length * (ft) | 16.40-32.81 | 16.40-32.81 | 16.40-32.81 | 16.40-32.81 | 16.40-32.81 |
| Net weight* (t) | 3-6 | 3-6,5 | 3,5-7 | 3,5-7,5 | 3,5-7,5 |

* p-arametry zależne od konfiguracji maszyny